## **MULE**<sup>™</sup> 4000







_	_		_	_
D	n	MA		D
г		w	г	П

4-stroke, 2-cylinder, OHV 90° V Liquid-cooled **Engine** 

Displacement 617cc

**Maximum Torque** 34.7 lb-ft @ 2500 rpm

**Bore x Stroke** 2.99x2.68 in

**Compression Ratio** 10:3:1

**Fuel System** DFI® with 34mm Mikuni throttle body

**Transmission** Continuously Variable Transmission (CVT) with (H,N,R)

**Final Drive** 2WD, shaft. Dual mode rear differential with

differential lock

**Engine Braking** No

**Alternator Output** 

(max)

23 amp

## **CAPABILITY**

MacPherson Strut/3.9 in Front Suspension / **Wheel Travel** 

Rear Suspension /

DeDion Axle/2.8 in

**Wheel Travel** 

**Front Tires** 

23x11.00-10 23x11.00-10

**Rear Tires Steering** 

Rack-and-pinion

**Park Brake Type** 

Independent, Mechanical Drum

**Front Brakes** 

Drum

**Rear Brakes** Drum

**Ground Clearance** 7.5 in **Fuel Capacity** 6.3 gal

**Turning Radius** 11.0 ft

**Cargo Bed** 46.3 x 51.6 x 11.4 in

**Dimensions** (LxWxH)

**Cargo Bed Load** 800 lb

**Capacity** 

**Payload Capacity** 1327 lb

**Seating Capacity** 

**Towing Capacity** 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

## **DETAILS**

**Overall Length** 116.7 in

**Overall Width** 62.0 in

**Overall Height** 75.8 in

**Curb Weight** 1338.4 lb\*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

**Color Choices** Dark Royal Red

Kawasaki 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.

