## **MULE™ 4010 4x4**









## **POWER**

Engine 4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear

differential with differential lock

Engine Braking No

Alternator Output 23 amp

(max)

Rear Brakes Drum

Ground Clearance 6.9 in

Fuel Capacity 6.3 gal

Turning Radius 11.2 ft

Cargo Bed Dimensions

**Cargo Bed Load** 

46.3 x 51.6 x 11.4 in

(LxWxH)

800 lb

**Capacity** 

Payload Capacity 1327 lb

**Seating Capacity** 

Towing Capacity 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

## CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Steering Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

## **DETAILS**

Overall Length 116.7 in
Overall Width 62.0 in

Overall Height 75.8 in

Curb Weight 1433.3 lb\*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Wheel Type Steel

Color Choices Timberline Green, Dark Royal Red

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

