


2021


MULE PRO-DXT™ DIESEL



SUPER BLACK



| POWER                           |   | Ground Clearance             | 10.2 in  |
|---------------------------------|---|------------------------------|--|
| Engine                          | 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel                              | Fuel Capacity                | 7.9 gal  |
| Displacement                    | 993cc   | Turning Radius               | 16.0 ft  |
| Maximum Torque                  | 38.3 lb-ft @ 2400 rpm   | Cargo Bed Dimensions (LxWxH) | 42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-person)   |
| Bore x Stroke                   | 2.91x3.03 in  | Cargo Bed Load Capacity      | 1000 lb (3-person)350 lb (6-person)  |
| Compression Ratio               | 23.5:1  | Payload Capacity             | 1581 lb  |
| Fuel System                     | Bosch in-line injection pump  | Seating Capacity             | 3-person (1 row), 6 person (2 row)   |
| Transmission                    | Continuously Variable Transmission (CVT) with (H,L,N,R)                       | Towing Capacity              | 2000 lb  |
| Final Drive                     | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock | Lighting                     | (2) Halogen headlights.  |
| Engine Braking                  | Yes   | DETAILS                      |  |
| Alternator Output (max)         | 55 amp  | Overall Length               | 133.3 in   |
| CAPABILITY                      |   | Overall Width                | 64.0 in  |
| Front Suspension / Wheel Travel | Double wishbone/8.7 in  | Overall Height               | 77.6 in  |
| Rear Suspension / Wheel Travel  | Double wishbone/8.5 (L) /8.7 (R) in   | Curb Weight                  | 1922.8 lb*   |
| Front Tires                     | 26x9.00-12  | Wheelbase                    | 92.3 in  |
| Rear Tires                      | 26x11.00-12   | Instruments                  | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps |
| Steering                        | Rack-and-pinion, Tilt steering  | Color Choices                | Super Black  |
| Park Brake Type                 | Independent, Mechanical Disc  | Warranty                     | Kawasaki 3-Year Limited Warranty   |
| Front Brakes                    | Dual Disc, 2 piston caliper   |                              |  |
| Rear Brakes                     | Dual Disc, 1 piston caliper   |                              |  |



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [guam.kawasaki-la.com](http://guam.kawasaki-la.com) for full product details.