MULE PRO-FX™







	N	N	M	Œ	D
	U	ľ	ľ	E	Л

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83 x 2.62 in

Compression Ratio 9.5:

Fuel System DFI® with 34mm throttle body

75 amp

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

Alternator Output

(max)

Turi

Turning Radius 16.0 ft

Cargo Bed Dimensions

Fuel Capacity

Ground Clearance

Dimensions (LxWxH)

54.1 x 53.3 x 11.0 in

1000 lb (600 lb for California models)

Cargo Bed Load

Capacity

10.4 in

7.9 gal

Payload Capacity 1616 lb

Seating Capacity 3

Towing Capacity 2000 lb

Lighting (2) Halogen headlights.

CAPABILITY

Front Suspension / Double wishbone/8.7 in Wheel Travel

Rear Suspension / Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12, radial

26x11.00-12, radial

Rear Tires Steering

Rack-and-pinion

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.4 in

Curb Weight 1816.9 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt

reminder lamps

Color Choices Super Black

Warranty Kawasaki 3-Year Limited Warranty



