
## **MULE PRO-FX™ EPS**









## **POWER**

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83 x 2.62 in

Compression Ratio 9.5:

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

**Alternator Output** 

(max)

75 amp

## **CAPABILITY**

Front Suspension / Double wishbone / 8.7 in Wheel Travel

Rear Suspension / Wheel Travel Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x

26x9.00-12, radial

**Rear Tires** 26x11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

**Front Brakes** 

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Ground Clearance 10.4 in

Fuel Capacity 7.9 gal
Turning Radius 16.0 ft

Cargo Bed Dimensions 54.1 x 53.3 x 11.0 in

Dimensions (LxWxH)

Cargo Bed Load Capacity

1000 lb (600 lb for California models)

Payload Capacity 1616 lb

Seating Capacity 3

Towing Capacity 2000 lb

Lighting (2) Halogen headlights.

## **DETAILS**

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.4 in

Curb Weight 1830.2 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

Color Choices Timberline Green, Bright White

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

