MULE SX™ 4x4 XC FI









Drum

8.1 in

11.8 ft

400 lb

POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2400 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio

Fuel System Fuel injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

22.9 amp

Engine Braking

Alternator Output

(max)

Fuel Capacity 4.2 gal **Turning Radius Cargo Bed** 35.6 x 40.9 x 9.6 in **Dimensions** (LxWxH)

Ground Clearance

Rear Brakes

Cargo Bed Load Capacity

900 lb **Payload Capacity**

Seating Capacity

Towing Capacity 1100 lb*

Lighting (2) Halogen headlights, tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.1 in **Wheel Travel**

Rear Suspension /

Unit Swingarm/3.1 in

Wheel Travel Front Tires

26x9.00-12

Rear Tires

26x9.00-12

Steering

Rack-and-pinion, Tilt steering

Park Brake Type

Independent, Mechanical Drum

Front Brakes Drum

DETAILS

Warrantv

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 73.4 in

Curb Weight 1082.7 lb**

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

Color Choices Vibrant Blue, Timberline Green

Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

