## MULE SX™ 4x4 XC FI









## **POWER**

**Engine** 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

**Maximum Torque** 21.4 lb-ft @ 2400 rpm

**Bore x Stroke** 3.23x2.99 in

**Compression Ratio** 

**Fuel System** Fuel injection

**Transmission** Continuously Variable Transmission (CVT) with (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** 

**Alternator Output** 

(max)

22.9 amp

Rear Brakes	Drum
Ground Clearance	8.1 in
Fuel Capacity	4.2 gal
Turning Radius	11.8 ft
Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Cargo Bed Load Capacity	400 lb
Payload Capacity	900 lb
Seating Capacity	2
<b>Towing Capacity</b>	1100 lb*
Lighting	(2) Halogen headlights, tail/brake lights

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.1 in **Wheel Travel** 

**Rear Suspension /** 

Unit Swingarm/3.1 in

**Wheel Travel** 

**Front Tires Rear Tires** 

26x9.00-12

Steering

26x9.00-12

**Park Brake Type** 

Rack-and-pinion, Tilt steering

Independent, Mechanical Drum

**Front Brakes** Drum

## **DETAILS**

**Overall Length** 106.7 in **Overall Width** 52.6 in **Overall Height** 73.4 in **Curb Weight** 1082.7 lb\*\* Wheelbase 70.1 in Instruments Fuel gauge, hour meter, oil temp light, parking brake Vibrant Blue, Timberline Green **Color Choices** Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

