## NEW 2021 TERYX KRX® 1000 TRAIL EDITION





FRAGMENT CAMO GRAY

40.0 ----



## POWER

| Engine            | 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled      |
|-------------------|---|
| Displacement      | 999cc   |
| Maximum Torque    | 76.7 lb-ft @ 7000 rpm                                     |
| Bore x Stroke     | 92.0 x 75.1 mm  |
| Compression Ratio | 11.5:1  |
| Fuel System       | DFI with two 50mm throttle bodies                         |
| Ignition          | TCBI with electronic advance                              |
| Starting System   | Electric  |
| Transmission      | Automatic CVT with centrifugal clutch (H,L,N,R)           |
| Final Drive       | Selectable 2WD/4WD with locking front differential, shaft |
| Engine Braking    | Yes   |

## CAPABILITY

| Front Suspension /<br>Wheel Travel | Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in.                     |
|------------------------------------|--|
| Rear Suspension /<br>Wheel Travel  | 4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in. |
| Front Tires                        | MAXXIS Carnivore 31 x 10.00R15 8PR   |
| Rear Tires                         | MAXXIS Carnivore 31 x 10.00R15 8PR   |
| Steering                           | Electric Power Steering (EPS) / rack-and-pinion  |
| Front Brakes                       | Dual hydraulic discs with two-piston calipers  |
| Rear Brakes                        | Dual hydraulic discs with single-piston calipers   |
| Ground Clearance                   | 13.6 in  |
|                                    |  |

| Fuel Capacity                   | 10.6 gal  |
|---------------------------------|---|
| Turning Radius                  | 20.3 ft   |
| Cargo Bed<br>Dimensions (LxWxH) | 14.6 x 33.1 x 9.1 in                                  |
| Cargo Bed Load<br>Capacity      | 351 lbs   |
| Payload Capacity                | 781 lbs   |
| Seating Capacity                | 2   |
| Towing Capacity                 | N/A   |
| Lighting                        | (2) LED headlights, (2) LED taillights, LED stoplight |
|                                 |   |

## **DETAILS**

Fuel Canadity

| Frame          | Ladder type, tubular steel  |
|----------------|---|
| Overall Length | 133.3 in  |
| Overall Width  | 68.1 in   |
| Overall Height | 76.6 in   |
| Curb Weight    | 2019.8 lbs (2022.0 CA)*   |
| Wheelbase      | 98.8 in   |
| Instruments    | Multi-function digital meter with bar-style tachometer (2<br>display options), digital speedometer, bar-style fuel<br>gauge, gear indicator (L, H, N, R), Power Mode, driving<br>mode (2WD/4WD/4WD+Diff Lock) indicator, Economical<br>Riding Indicator, clock, odometer, dual trip meters, hour<br>meter, water temperature, digital battery gauge, bar-style<br>CTV temperature, seatbelt warning lamp, oil warning lamp,<br>engine check lamp, water temperature warning lamp,<br>neutral indicator lamp, reverse indicator lamp, parking<br>indicator lamp, EPS warning lamp, and CVT belt warning<br>lamp. |
| Color Choices  | Fragment Camo Gray  |
| Warranty       | 6 months  |





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit guam.kawasaki-la.com for full product details.