TERYX4™ S CAMO







POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft@ 5500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

Fuel System DFI® with two 36mm Mikuni throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

Standard Ground
Clearance/Maximum

11.2 in / 12.2 in

Fuel Capacity 7.9 gal

Ground Clearancet

Turning Radius 17.7 ft.

Cargo Bed 17.9 x 47.6 x 8.7 in Dimensions (LxWxH)

Cargo Bed Load 249 lb

Capacity

Payload Capacity 1096 lb

Seating Capacity 4

tillig cupacity 4

Towing Capacity 1300 lb

Lighting (4) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping / 10.7 in.

Rear Suspension / Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully wheel Travel adjustable preload, and adjustable compression

damping / 10.0 in.

Front Tires Maxxis 27 x 9-14

Rear Tires Maxxis 27 x 11-14

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

DETAILS

Frame Steel Tube Double-X Reinforcement

Overall Length 125.4 in

Overall Width 62.6 in

Overall Height 80.5 in

Curb Weight 1642.7 lb*

Wheelbase 88.2 in

Instruments Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and

parking-brake indicator, R/N/P/4WD, water temp and

low-oil-pressure indicators

Wheel Type Allo

Color Choices Realtree Xtra® Green Camo

Warranty Kawasaki 3-Year Limited Warranty



