## <sup>2021</sup> TERYX4<sup>™</sup> S CAMO





REALTREE XTRA® GREEN CAMO



## POWER

| Engine            | 4-stroke, SOHC, 4-valve V-twin, liquid-cooled             |
|-------------------|---|
| Displacement      | 783cc   |
| Maximum Torque    | 47.0 lb-ft@ 5500 rpm                                      |
| Bore x Stroke     | 85.0 x 69.0mm   |
| Compression Ratio | 10.7:1  |
| Fuel System       | DFI® with two 36mm Mikuni throttle bodies                 |
| Ignition          | TCBI with electronic advance                              |
| Starting System   | Electric  |
| Transmission      | Automatic CVT with centrifugal clutch (H,L,N,R)           |
| Final Drive       | Selectable 2WD/4WD with locking front differential, shaft |
| Engine Braking    | Yes   |

| Standard Ground<br>Clearance/<br>Maximum Ground<br>Clearance† | 11.2 in / 12.2 in                                     |
|---|---|
| Fuel Capacity   | 7.9 gal   |
| Turning Radius  | 17.7 ft.  |
| Cargo Bed<br>Dimensions (LxWxH)                               | 17.9 x 47.6 x 8.7 in                                  |
| Cargo Bed Load<br>Capacity                                    | 249 lb  |
| Payload Capacity  | 1096 lb   |
| Seating Capacity  | 4   |
| Towing Capacity   | 1300 lb   |
| Lighting  | (4) LED headlights, (2) LED taillights, LED stoplight |
|   |   |

## CAPABILITY

| Front Suspension /<br>Wheel Travel | Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping / 10.7 in. |
|------------------------------------|--|
| Rear Suspension /<br>Wheel Travel  | Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping / 10.0 in. |
| Front Tires                        | Maxxis 27 x 9-14   |
| Rear Tires                         | Maxxis 27 x 11-14  |
| Steering                           | Electric Power Steering (EPS) / rack-and-pinion  |
| Front Brakes                       | Dual hydraulic discs with two-piston calipers  |
| Rear Brakes                        | Sealed, oil-bathed, multi-disc   |
|                                    |  |

## DETAILS

| Frame          | Steel Tube Double-X Reinforcement   |
|----------------|---|
| Overall Length | 125.4 in  |
| Overall Width  | 62.6 in   |
| Overall Height | 80.5 in   |
| Curb Weight    | 1642.7 lb*  |
| Wheelbase      | 88.2 in   |
| Instruments    | Multi-function digital meter with speedometer, fuel<br>gauge, clock, hour meter, odometer, dual trip meter and<br>parking-brake indicator, R/N/P/4WD, water temp and<br>low-oil-pressure indicators |
| Color Choices  | Realtree Xtra® Green Camo   |
| Warranty       | Kawasaki 3-Year Limited Warranty  |





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit guam.kawasaki-la.com for full product details.