2023 **KLR**[®]650 S







130/80-17

POWER

			Front Brakes	Single 300mm disc with 2-piston calipers	
	Engine	4-Stroke, single cylinder, DOHC		(and ABS)	
	Displacement	652cc	Rear Brakes	Single 240mm disc with single-piston caliper (and ABS)	
	Bore x Stroke	100.0 x 83.0mm			
	Compression Ratio	9.8:1	DETAILS		
	Maximum Torque	39.1 lbft. @ 4,500rpm	Frame Type	Tubular, Semi-Double Cradle	
			Rake/Trail	29.5°/4.6 in	
	Fuel System	DFI w/40mm Throttle Body	Overall Length	88.8 in	
	Ignition	CDI	Overall Width	38.2 in	
	Transmission	5-speed, return shift with wet multi-disc manual clutch	Overall Height	56.3/54.9 in (screen hi/lo)	
	Final Drive	Sealed Chain	Ground Clearance	7.3 in	
PERFORMANCE		Seat Height	32.1 in		
			Curb Weight	Non-ABS: 456.2 lb. / ABS: 460.6 lb*	

Rear Tire

Front Suspension /	41mm telescopic fork/ 6.7 in	Fuel Capacity	6.1 gal
Wheel Travel		Wheelbase	59.6 in
Rear Suspension / Wheel Travel	Uni-Trak® single shock with adjustable rebound damping and adjustable spring preload/ 7.0 in	Color Choices	Pearl Storm Gray, Candy Lime Green
wheet mavel	pretoad/ 7.0 m	Warranty	12 Months
Front Tire	90/90-21		



F



20

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit guam.kawasaki-la.com for full product details.