


2023

# KLX<sup>®</sup>300SM

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



## POWER

<b>Engine</b>	4-stroke single, DOHC, liquid-cooled
<b>Displacement</b>	292cc
<b>Bore x Stroke</b>	78.0 x 61.2mm
<b>Compression Ratio</b>	11.1:1
<b>Fuel System</b>	DFI <sup>®</sup> with 34mm Keihin throttle body
<b>Ignition</b>	CDI
<b>Transmission</b>	6-speed, return shift with wet multi-disc manual clutch
<b>Final Drive</b>	Chain

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	43mm inverted cartridge fork with adjustable compression damping / 9.1 in
<b>Rear Suspension / Wheel Travel</b>	Uni-Trak <sup>®</sup> gas charged shock with piggyback reservoir with adjustable rebound damping and spring preload/ 8.1 in
<b>Front Tire</b>	110/70-17

<b>Rear Tire</b>	130/70-17
<b>Front Brakes</b>	Single 300mm petal disc with a dual-piston caliper
<b>Rear Brakes</b>	Single 240mm petal disc with single-piston caliper

## DETAILS

<b>Frame Type</b>	Semi Double Cradle
<b>Rake/Trail</b>	25.0° / 2.8 in
<b>Overall Length</b>	86.4 in
<b>Overall Width</b>	31.1 in
<b>Overall Height</b>	45.1 in
<b>Ground Clearance</b>	9.3 in
<b>Seat Height</b>	33.9 in
<b>Curb Weight</b>	304.3 lb*
<b>Fuel Capacity</b>	2.0 gal
<b>Wheelbase</b>	56.5 in
<b>Color Choices</b>	Lime Green/Ebony, Ebony
<b>Warranty</b>	12 Months

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [guam.kawasaki-la.com](http://guam.kawasaki-la.com) for full product details.