

2023

KX™ 450



POWER		Front Tire	80/100-21
Engine	4-stroke single, DOHC, liquid-cooled	Rear Tire	120/80-19
Displacement	449cc	Front Brakes	Single semi-floating 270mm Braking® petal disc with dual-piston caliper
Bore x Stroke	96.0 x 62.1mm	Rear Brakes	Single 250mm Braking® petal disc with single-piston caliper
Compression Ratio	12.5:1	DETAILS	
Fuel System	DFI® with 44mm Keihin throttle body	Frame Type	Aluminum perimeter
Ignition	Digital CDI with 3 Coupler Options	Rake/Trail	27.6° / 4.8 in
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation	Overall Length	86.0 in
Final Drive	Chain	Overall Width	32.3 in
PERFORMANCE		Overall Height	49.8 in
Front Suspension / Wheel Travel	49mm inverted telescopic coil-spring fork with 16-way compression damping and 16-way rebound damping/12.0 in	Ground Clearance	13.4 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with dual-range (4 turns stepless high speed/19-way low-speed) compression damping, 22-way rebound damping and adjustable preload/12.1 in	Seat Height	37.6 in
		Curb Weight	233.2 lb without fuel / 243.3 lb*
		Fuel Capacity	1.64 gal
		Wheelbase	58.5 in
		Color Choices	Lime Green
		Warranty	Not Available



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit guam.kawasaki-la.com for full product details.