KX[™]450X









Single semi-floating 270mm Braking® petal

Single 240mm Braking® petal disc with

disc with dual-piston caliper

single-piston caliper

POWER

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 449cc

96.0 x 62.1mm **Bore x Stroke**

Compression

Ratio

12.5:1

DFI® with 44mm Keihin throttle body **Fuel System**

Ignition Digital CDI with 3 Coupler Options

Transmission 5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation

Final Drive Chain

DETAILS

Front Tire

Rear Tire

Front Brakes

Rear Brakes

Frame Type Aluminum perimeter

80/100-21

120/90-18

27.6° / 4.7 in Rake/Trail

Overall Length 86.0 in

Overall Width 32.3 in

Overall Height 49.8 in

Ground Clearance 13.2 in

Seat Height 37.4 in

Curb Weight 235.8 lb without fuel / 246.0 lb*

Fuel Capacity 1.64 gal

Wheelbase 58.5 in

Color Choices Lime Green

Warranty Not Available

PERFORMANCE

Front Suspension / **Wheel Travel** 49mm inverted telescopic coil-spring fork with 16-way compression damping and 16way rebound damping/12.0 in

Suspension / **Wheel Travel** Uni-Trak® gas charged shock with piggyback reservoir with dual-range (4 turns stepless high speed/19-way low-speed) compression damping, 22-way rebound damping and adjustable preload/12.1 in

Scan with camera to view videos. key features and more.

