MULE PRO-FX™ EPS LE







POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Ground Clearance 10.4 in

Fuel Capacity Turning Radius

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

DETAILS

Overall Length

Overall Width

Overall Height

7.9 gal

16.0 ft

54.1 x 53.3 x 11.0 in

999 lb / 600.0 lb CA Model

1,616.3 lb / 1,263.5 for CA Model

2,000 lb

133.3 in

64.0 in

79.7 in

1,832.4 lb*

(2) Halogen headlights. (2) LED headlights

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Dual Disc, 2 piston caliper

Rear Suspension / **Wheel Travel**

Steering

Front Brakes

Double wishbone/8.5 in (L) /8.7 in (R)

Front Tires 26x9.00-12, radial

Rear Tires 26x11.00-12, radial

Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Rear Brakes Dual Disc, 1 piston caliper Wheelbase

Curb Weight

Instruments

92.3 in

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning

indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Additional Features Roof, Cast Aluminum Wheels

Color Choices Firecracker Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

