MULE PRO-FXT™ RANCH EDITION







POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

DFI® with 34mm throttle body **Fuel System**

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

CAPABILITY

75 amp

Double wishbone/8.7 in

Double wishbone/8.5 (L) /8.7 (R) in

Rear Suspension /

Front Suspension /

Wheel Travel

Wheel Travel

Front Tires 26x9.00-12, radial

Rear Tires 26x11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper **Ground Clearance** 10.0 in

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

Dimensions (LxWxH) person)

Cargo Bed Load

Capacity

Fuel Capacity

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

7.9 gal

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2.000 lb

(2) Halogen headlights. (2) LED headlights Lighting

DETAILS

Overall Length 135.6 in

Overall Width 64.0 in

Overall Height 79.5 in

Curb Weight 1,971.3 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

and parking indicators, seatbelt reminder lamps

Additional Features Roof, WARN® VRX 45 Winch, Premium Seats, Front Bumper

Plates

Color Choices Metallic Titanium

Warranty Kawasaki STRONG 3-Year Limited Warranty



