MULE PRO-FXT™ RANCH EDITION







POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

DFI® with 34mm throttle body **Fuel System**

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Final Drive

with differential lock

Engine Braking Yes

Alternator Output

(max)

48.0 lb-ft @ 3,500 rpm

Selectable 2WD/4WD, shaft. Dual mode rear differential

75 amp

CAPABILITY

Double wishbone/8.7 in

Rear Suspension /

Front Suspension /

Wheel Travel

Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires

26x9.00-12, radial 26x11.00-12, radial

Rear Tires Steering

Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Ground Clearance 10.0 in

Turning Radius 16.0 ft

Cargo Bed

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-Dimensions (LxWxH)

7.9 gal

person)

Cargo Bed Load

Fuel Capacity

Capacity

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

3-person (1 row), 6 person (2 row)

Towing Capacity

Seating Capacity

2.000 lb

Lighting (2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 135.6 in

Overall Width 64.0 in

Overall Height 79.5 in

Curb Weight 1,971.3 lb*

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator,

oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

Additional Features

Roof, WARN® VRX 45 Winch, Premium Seats, Front Bumper

Plates

Color Choices

Metallic Titanium

Warranty

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

