

2023

NINJA<sup>®</sup> ZX™-4RR KRT EDITION

Kawasaki

Let the Good Times Roll<sup>®</sup>



 LIME GREEN/EBONY



POWER		Rear Tire	160/60 - 17
Engine	4-stroke, In-Line Four, OHC, 16-valve, liquid-cooled	Front Brakes	Dual 290mm discs, ABS
Displacement	399cc	Rear Brakes	Single 220mm disc, ABS
Bore x Stroke	57.0 x 39.1mm	DETAILS	
Compression Ratio	12.3:1	Frame Type	Trellis, high-tensile steel
Fuel System	DFI <sup>®</sup> w/ 34mm throttle valves (4)	Rake/Trail	23.5° / 3.8 in.
Ignition	Digital	Overall Length	78.3 in.
Transmission	6-speed, manual, return shift	Overall Width	30.1 in.
Final Drive	Chain	Overall Height	43.7 in.
Electronic Rider Aids	Kawasaki TRaction Control (KTRC) (3-mode), Kawasaki Quick Shifter (KQS) (dual direction)	Ground Clearance	5.3 in.
PERFORMANCE		Seat Height	31.5 in.
Front Suspension / Wheel Travel	37mm inverted fork with SFF-BP internals and spring preload adjustability/4.7 in.	Curb Weight	414.5 lb*
Rear Suspension / Wheel Travel	Horizontal Back-link, BFRC lite gas charged shock w/ piggyback reservoir, adjustable compression, rebound and spring preload/4.9 in.	Fuel Capacity	4.0 gal.
Front Tire	120/70 - 17	Wheelbase	54.3 in.
		Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity using RIDELOGY THE APP
		Color Choices	Lime Green/Ebony
		Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [guam.kawasaki-la.com](http://guam.kawasaki-la.com) for full product details.