²⁰²³ NINJA[®] ZX[™]-4RR KRT EDITION





LIME GREEN/EBONY

POWER

Engine	4-stroke, In-Line Four, OHC, 16-valve, liquid- cooled
Displacement	399cc
Bore x Stroke	57.0 x 39.1mm
Compression Ratio	12.3:1
Fuel System	DFI® w/ 34mm throttle valves (4)
Ignition	Digital
Transmission	6-speed, manual, return shift
Final Drive	Chain
Electronic Rider Aids	Kawasaki TRaction Control (KTRC) (3-mode), Kawasaki Quick Shifter (KQS) (dual direction)

Rear Tire160/60 - 17Front BrakesDual 290mm discs, ABSRear BrakesSingle 220mm disc, ABS

DETAILS

	Frame Type	Trellis, high-tensile steel
	Rake/Trail	23.5°/3.8 in.
	Overall Length	78.3 in.
	Overall Width	30.1 in.
	Overall Height	43.7 in.
de),	Ground Clearance	5.3 in.
tion)	Seat Height	31.5 in.
	Curb Weight	414.5 lb*
	Fuel Capacity	4.0 gal.
5	Wheelbase	54.3 in.
ed e	Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity using RIDEOLOGY THE APP
	Color Choices	Lime Green/Ebony
	Warranty	12 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel	37mm inverted fork with SFF-BP internals and spring preload adjustability/4.7 in.
Rear Suspension / Wheel Travel	Horizontal Back-link, BFRC lite gas charged shock w/ piggyback reservoir, adjustable compression, rebound and spring preload/4.9 in.
Front Tire	120/70 - 17

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit guam.kawasaki-la.com for full product details.