2024 **BRUTE FORCE® 300**









POWER			Fuel Capacity	3.2 gal
	Engine	4-stroke, 1-cylinder, SOHC	Electronic Power Steering (EPS)	No
	Displacement	271cc	Turning Radius	9.2 ft
	Bore x Stroke	72.7 x 65.2mm	Towing Capacity	500 lb
	Compression Ratio	11.0:1	Total Rack	110 lb
	Maximum Torque	15.9 lb-ft @ 6,500 rpm	Capacity Rack Capacity,	44/66 lb
	Fuel System	Keihin CVK32 carburetor	Front/Rear	44/00 10
	Ignition	DC-CDI	Lighting	(2) 35W headlights, 5W taillight and 21W stoplight
	Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	DETAILS	
	Final Drive	2WD, Shaft		

CAPABILITY

Front Suspension / Wheel Travel	Independent double wishbone/5.2 in		
Rear Suspension / Wheel Travel	Swingarm/5.6 in		
Front Tires	AT 22 x 7-10 Maxxis® tubeless		
Rear Tires	AT 22 x 10-10 Maxxis® tubeless		
Front Brakes	Dual 148mm discs		
Rear Brakes	Single 148mm disc		
Ground Clearance	6.1 in		
Starting System	Electric		

Frame Type	Double cradle, steel		
Track Front/Rear	33.5/32.7 in		
Overall Length	75.4 in		
Overall Width	42.5 in		
Overall Height	46.1 in		
Seat Height	33.3 in		
Curb Weight	535.8 lb*		
Wheelbase	45.9 in		
Instruments	Speedometer, odometer, clock, fuel gauge and coolant temp light		
Color Choices	Firecracker Red, Grayish Blue		
Warranty	12 Month Limited Warranty		



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit guam.kawasaki-la.com for full product details.