

2024 KLX®110R

Kawasaki
Let the Good Times Roll®



POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	112cc
Bore x Stroke	53.0 x 50.6mm
Compression Ratio	9.5:1
Fuel System	18mm Keihin carburetor and screw type throttle limiter on grip housing
Ignition	DC-CDI
Transmission	4-speed, return shift, automatic centrifugal and wet, multi-disc clutch
Final Drive	Chain

Rear Tire	3.00 x 12
Front Brakes	90mm mechanical drum, cable actuated
Rear Brakes	110mm mechanical drum, rod actuated

DETAILS

Frame Type	Backbone frame, high-tensile steel
Rake/Trail	24.8° / 2.0 in
Overall Length	61.4 in
Overall Width	25.6 in
Overall Height	37.6 in
Ground Clearance	8.5 in
Seat Height	26.8 in
Curb Weight	167.5 lb*
Fuel Capacity	1.0 gal
Wheelbase	42.3 in
Color Choices	Lime Green, Battle Gray
Warranty	6 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel	30mm hydraulic telescopic fork/4.3 in
Rear Suspension / Wheel Travel	Swingarm with single hydraulic shock/4.3 in
Front Tire	2.50 x 14

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit guam.kawasaki-la.com for full product details.