²⁰²⁴ **KX[™]250**







POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	249cc
Bore x Stroke	78.0 x 52.2mm
Compression Ratio	14.1:1
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors
Ignition	Digital CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain
Electronic Rider Aids	Launch Control Mode

Front Tire80/100-21Rear Tire110/90-19Front BrakesSingle semi-floating 270mm Braking petal
disc with dual-piston caliperRear BrakesSingle 240mm Braking petal disc with
single-piston caliper

DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	28.0°/4.6 in
Overall Length	86.2 in
Overall Width	32.3 in
Overall Height	50.0 in
Ground Clearance	13.6 in
Seat Height	37.8 in
Curb Weight	227.6 lb* without fuel / 237.7 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.5 in
Color Choices	Lime Green
Warranty	Not Available

PERFORMANCE

Front	48mm inverted telescopic coil-spring fork
Suspension /	with 23-way compression damping and 20-
Wheel Travel	way rebound damping /12.4 in
Rear Suspension / Wheel Travel	Uni-Trak [®] with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.4 in

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit guam.kawasaki-la.com for full product details.