





_	_			_	_
P	n	M	M	г	п
P		v	v		ĸ
	u			_	

Engine 2-stroke single with exhaust power valve (KIPS), liquid-cooled

Displacement 84cc

Bore x Stroke 48.5 x 45.8mm

Compression 10.9:1 (low speed) / 9.0:1 (high speed)

Ratio

28mm Keihin carburetor **Fuel System**

Ignition

CDI with Digital Advance

Transmission

6-speed, return shift, with wet multi-disc

manual clutch

Final Drive

Chain

PERFORMANCE

Front Suspension / **Wheel Travel** 36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / **Wheel Travel** Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in

Front Tire

70/100-17

Rear Tire 90/100-14 **Front Brakes** Single 220mm petal disc with dual-piston caliper Single 184mm petal disc with single-piston **Rear Brakes** caliper

DETAILS

Frame Type	High-tensile steel perimeter design with subframe member	
Rake/Trail	29°/3.8 in	
Overall Length	72.0 in	
Overall Width	30.1 in	
Overall Height	43.3 in	
Ground Clearance	11.4 in	
Seat Height	32.7 in	
Curb Weight	164.4 lb*	
Fuel Capacity	1.32 gal	
Wheelbase	49.8 in	
Color Choices	Lime Green	

Not Available





Warranty