MULE PRO-MX™ EPS CAMO







POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5,000 rpm

102.0 x 85.0mm **Bore x Stroke**

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with centrifugal

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

clutch, (H,L,N,R)

35.7 amp

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/8.6 in

Rear Suspension / **Wheel Travel**

Double wishbone/9.1 in

Front Tires

25 x 10.00-12, radial 25 x 10.00-12, radial

Rear Tires

Steering

Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Dual Disc, 1 piston caliper Rear Brakes

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

33.4 x 44.1 x 9.1 in

699 lb / 600 lb CA Model

Payload Capacity 1,200 lb

Seating Capacity

Towing Capacity 1,500 lb

Lighting (2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 110.0 in

Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1,598.6 lb* / 1,600.6 lb* CA Model

Wheelbase 78.9 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator,

EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

lamps

Additional Features

Color Choices TRUETIMBER® STRATA

Kawasaki STRONG 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.

