

2024

TERYX® KRX4™ 1000 SE eS



METALLIC FLAT RAW GRAYSTONE



POWER		DETAILS	
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Fuel Capacity	10.6 gal
Displacement	999cc	Turning Radius	23.3 ft
Maximum Torque	76.7 lb-ft @ 7,000 rpm	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Bore x Stroke	92.0 x 75.1mm	Cargo Bed Load Capacity	351 lb
Compression Ratio	11.5:1	Payload Capacity	1,001 lb
Fuel System	DFI® with two 50mm throttle bodies	Seating Capacity	4
Ignition	TCBI with Electronic Advance	Towing Capacity	N/A
Starting System	Electric	Lighting	(2) LED headlights, (2) LED taillights, LED stoplight
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)		
Final Drive	Selectable 2WD/4WD with locking front differential, shaft		
Engine Braking	Yes		
CAPABILITY			
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in	Frame	Ladder type, tubular steel
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in	Overall Length	157.3 in
Front Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Overall Width	68.1 in
Rear Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Overall Height	79.3 in
Steering	Electric Power Steering (EPS) / rack-and-pinion	Curb Weight	2,207.2 lb* / 2,209.4 lb* CA Model
Front Brakes	Dual hydraulic discs with two-piston calipers	Wheelbase	125.8 in
Rear Brakes	Dual hydraulic discs with single-piston calipers	Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp.
Ground Clearance	14.4 in (max), 13.6 in (std)	Additional Features	Roof, Hifonics® Bluetooth®/AM/FM Audio System, WARN® VRX 45 Winch
		Color Choices	Metallic Flat Raw Graystone
		Warranty	6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit guam.kawasaki-la.com for full product details.