


2025

RIDGE® CREW HVAC

Kawasaki
Let the Good Times Roll®



 CANDY PERSIMMON RED



POWER		FUEL CAPACITY	
Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled	Fuel Capacity	12.9 gal
Displacement	999cc	Turning Radius	19.0 ft
Maximum Horsepower	92.0 hp¹ @ 8,500 rpm	Cargo Bed Dimensions (LxWxH)	34.6 x 49.0 x 12.8 in
Maximum Torque	65.8 lb-ft @ 5,500 rpm	Cargo Bed Load Capacity	1,000/600 lb CA Model
Bore x Stroke	73.4 x 59.0mm	Payload Capacity	1,444/1,290 lb CA Model
Compression Ratio	10.6:1	Seating Capacity	6-person (2 row), bench seats
Fuel System	EFI	Towing Capacity	2,500 lb
Ignition	TCBI with Digital Advance	Lighting	All-LED lighting
Starting System	Electric	DETAILS	
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Frame	Ladder type, tubular steel
Final Drive	Selectable 4WD with locking rear differential, shaft	Overall Length	155.3 in
Engine Braking	Yes	Overall Width	64.0 in
Alternator Output (max)	85 amp	Overall Height	81.5 in
Electronic Rider Aids	Power Modes, Economical Riding Indicator	Estimated Dry Weight	2,368.2/2,370.4 lb** CA Model
CAPABILITY		Curb Weight	2,478.4/2,480.6 lb* CA Model
Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Wheelbase	122.2 in
Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Front Tires	Duro 27 x 9-14	Additional Features	Full Cab with HVAC, Adjustable driver's seat, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP Powersports, USB ports, KQR™ system compatible
Rear Tires	Duro 27 x 11-14	Color Choices	Candy Persimmon Red
Wheel Type	14" Aluminum	Warranty	Kawasaki STRONG 3-Year Limited Warranty
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers		
Ground Clearance	13.2/13.8 in (max preload); 13.2 in CA Model		

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
Specifications subject to change. Visit guam.kawasaki-la.com for full product details.